

Product Specification

Name: Housing
Model: OGA1711
Material: QT40-5
Weight: 1.6kg

• Purpose: Lower Housing

• Applicable To: 336/50 Hydraulic Cylinder

Product Description

336/50 Hydraulic Housing(lower)

液 缸部件

活塞杆, 杆—— 接控制 芯 一起是液 缸的血管和心 部位. 向 体——控制液 活塞左,右 ,指示机 操作,便于 察全 和全 . 液 体——液 的指 腔室,控制 油,回油,左右方向,指 全 或全 . 活塞杆,杆-

接法 ——便于固定在 机支 体上,利用缸体来回 推,杆 叶片全 全.

Hydraulic cylinder component

Piston rod, toothed rod - Connecting the control spool group together are the blood vessels and heart parts of the hydraulic cylinder.

Guide housing - control the hydraulic piston left and right movement, drive the indicating mechanism operation, easy to observe the full open and close.

Hydraulic shell - hydraulic transmission command chamber, control oil inlet, oil return, left and right direction, command full open or full close.

Connecting flange - easy to fix on the fan support body, using the cylinder block to adjust the push disk, the adjustment rod to drive the blade fully open and close.

上海依库机电设备 Shanghai YIKU Power Equipment Co., Ltd

8613916002258

657925203@qq.com



axialfanparts.com

5587 Dongchuan Road, Pudong New Area, Shanghai